

6020



DH-Series 4MP IR Network 2.8mm Wedge Camera



Features

- 1/3" 4Megapixel progressive scan CMOS
- Support H.264&MJPEG dual codec
- Max 20fps@4M(2688x1520), 30fps@3M(2304x1296)
- Smart Detection supported
- WDR(120dB),Day/Night(ICR), 3DNR,AWB,AGC,BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 2.8mm fixed lens
- 1/1 Alarm in/out, 1/1 audio in/out
- Max. IR LEDs Length 20m
- Micro SD memory , IP67, IK10, PoE

Camera		
Image Sensor	1/3"4Megapixel progressive scanCMOS	
Effective Pixels	2688(H)x1520(V)	
Scanning System	Progressive	
Electronic Shutter Speed	Auto/Manual, 1/3(4)-1/10000s	
Min. Illumination	0.01lux/F2.0(color),0lux/F2.0 (IR on)	
S/N Ratio	More than 50dB	
Video Output	N/A	
Camera Features		
Max. IR LEDs Length	20m	
Day/Night	Auto(ICR)/Color/B/W	
Backlight Compensation	BLC / HLC / WDR(120dB)	
White Balance	Auto/Sunny/Night/Outdoor/Customized	
Gain Control	Auto/Manual	
Noise Reduction	3D	
Privacy Masking	Up to 4 areas	
Lens		
Focal Length	2.8mm	
Max Aperture	F1.8(F2.0,F1.8)	
Focus Control	Manual	
Angle of View	H.84*(106*/56*)	
Lens Type	Fixed lens	
Mount Type	Board-in Type	
Video		
Compression	H.264/H.264H/H.264B/MJPEG	
Resolution	4M(2688x1520)/4M(2560x1440)/3M(2304x1296)/1080P(1920x1080)/1.3M(1280x960)/720P(1280x720)/ D1(704x576/704x480) /CIF(352x288/352x240)	
Frame Rate	Main Stream	4M(1-20fps)/3M(1-30fps)
	Sub Stream	D1/CIF(1 ~ 30fps)
	Third Stream	720P(1-20fps)
Bit Rate	H.264: 32K ~ 10Mbps	
Corridor Mode	Support	
Audio		
Compression	N/A	
Interface	N/A	
Smart Function (Only for -ASI model)		
Smart detection	Tripwire	
	Intrusion	
	Abandoned/Missing	
	Scene Change	
	Audio detect	
	Face detect	
Network		
Ethernet	RJ-45 (10/100Base-T)	
Wi-Fi	N/A	
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMR, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x	
Compatibility	ONVIF,PSIA,CGI	
Max. User Access	20 users	
Smart Phone	iPhone, iPad, Android, Windows Phone	
Auxiliary Interface		
Memory Slot	Micro SD Max 128GB	
RS485	N/A	
Alarm	1/1 channel In/Out	
PIR Sensor Range	N/A	
General		
Power Supply	DC12V, PoE (802.3af)	
Power Consumption	< 5W	
Working Environment	-30°C--+60°C, Less than 95% RH	
Ingress Protection	IP67	
Vandal Resistance	IK10	
Dimensions	Φ106mm×50.3mm	
Weight	0.35kg	

OUR LOCATION

1 300 N. FLORIDA MANGO RD
SUITE 14A
WEST PALM BEACH, FL 33409



CCTV AGENT

CONTACT INFO

TOLL FREE: 877.523.CCTV (2288)
MAIN : 561.249.4511
EMAIL : SALES@CCTVAGENT.COM