

# 8001



## Uniview 4MP WDR Network IR Mini Bullet Camera



### Features

- 4MP Progressive SCAN CMOS Image Sensor
- 3.6mm Fixed Lens
- H.265 / H.264 / MJPEG Video Compression
- Triple-Stream Encoding
- Smart IR, up to 30m IR distance
- 9:16 Corridor Format Option
- True 120dB Wide Dynamic Range
- ONVIF Conformance
- IP66 Ingress Protection Rating

| Camera                 |   |
|------------------------|---|
| Sensor                 | 1/3", 4.0 megapixel, progressive scan, CMOS   |
| Lens                   | 3.6mm@F1.8<br>Angle of view(H): 87°   |
| Shutter                | Auto/Manual, 1/6~1/8000 s   |
| Min. Illumination      | Colour: 0.02 Lux (F1.8, AGC ON)<br>0 Lux with IR on   |
| Day/Night              | IR-cut filter with auto switch (ICR)  |
| IR Range               | Up to 30m (98 ft) IR range  |
| S/N                    | >55dB   |
| WDR                    | 120dB   |
| Noise Reduction        | 2D/3D   |
| Video                  |   |
| Max. Resolution        | 2592x1520   |
| Video Compression      | H.265/H.264/MJPEG   |
| Frame Rate             | 4MP (2592x1520): Max. 20 fps; 4MP (2560x1440): Max. 25 fps<br>3MP (2048x1520): Max. 30 fps; 1080P (1920x1080): Max. 30 fps  |
| Video Streaming        | Triple  |
| 9:16 Corridor Mode     | Supported   |
| ROI                    | Supported   |
| OSD                    | Up to 8 OSDs  |
| Motion Detection       | Up to 2 areas   |
| Privacy Mask           | Up to 4 areas   |
| Network                |   |
| Protocols              | L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SNMP, SIP, QoS |
| Compatible Integration | ONVIF, API  |
| Interface              |   |
| Network                | 1 RJ45 10M/100M Base-TX Ethernet  |
| General                |   |
| Power                  | 12 V DC, or PoE (IEEE802.3 af)<br>Power consumption: Max 6.4 W  |
| Dimensions (L x W x H) | 157.3 x 62.4 x 63 mm (6.2" x 2.5" x 2.5")   |
| Weight                 | 0.45 kg (0.99 lb)   |
| Working Environment    | -35°C ~ +60°C (-31°F ~ 140°F), Humidity ≤ 95% RH(non-condensing)  |
| Ingress Protection     | IP66  |

### OUR LOCATION

1300 N. FLORIDA MANGO RD  
SUITE 14A  
WEST PALM BEACH, FL 33409



**CCTV**  
**AGENT**

### CONTACT INFO

TOLL FREE: 877.523.CCTV (2288)  
MAIN : 561.249.4511  
EMAIL : SALES@CCTVAGENT.COM