

6038



DH-Series 4MP IR Network 2.8mm Matrix Eyeball Camera




Features

- 1/3-in. 4 MP Progressive Scan CMOS
- Triple-stream Encoding with Smart H.265+ Compression
- 4 MP (2688 x 1520) at 30 fps
- Smart Detection Support
- True WDR (120 dB) and Day/Night IR Cut Filter
- Built-in Microphone
- 2.8 mm Fixed Lens
- Maximum IR LED Length 50 m (164 ft)
- Micro SD Memory, IP67, PoE

Camera	
Image Sensor	1/3" 4Megapixel progressive scan CMOS
Effective Pixels	2688(H)x1520(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual, 1/3(4)~1/100000s
Min. Illumination	0.01Lux/F2.0 (Color), 0Lux/F2.0(IR on)
S/N Ratio	More than 50dB
Video Output	N/A
Camera Features	
Max. IR LEDs Length	50m
Day/Night	Auto(ICR)/Color/B/W
Backlight Compensation	BLC / HLC / WDR(120dB)
White Balance	Auto/Sunny/Night/Outdoor/Customized
Gain Control	Auto/Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Lens	
Focal Length	2.8mm (3.6mm,6mm optional)
Max Aperture	F2.0(F2.0)
Focus Control	Manual
Angle of View	H:110*(81*/55*)
Lens Type	Fixed lens
Mount Type	Board-in Type
Video	
Compression	H.264/H.264H/H.264B/MJPEG
Resolution	4M(2688x1520)/4M(2560x1440)/1080P(1920x1080)/720P(1280x720) /D1(704x576/704x480) / CIF(352x288/352x240)
Frame Rate	Main Stream 4M(1~20fps)/3M(1~25/30fps) Sub Stream D1/CIF(1~20fps) Third Stream 720P(1~20fps)
Bit Rate	H.264: 32Kbps~10Mbps
Corridor Mode	Support
Audio	
Compression	G.711a/ G.711u/ AAC(only for -AS)
Interface	Built-in Mic(only for -AS)
Smart Function(Optional)	
	Tripwire Intrusion Abandoned Binion
	Face detect
Ethernet	RJ-45 (10/100Base-T)
Network	
Wi-Fi	N/A
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x
Compatibility	ONVIF, PSIA, CGI
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Auxiliary Interface	
Memory Slot	Micro SD Max 128GB(only for -AS)
RS485	N/A
Alarm	N/A
PIR Sensor Range	N/A
General	
Power Supply	DC12V, PoE (802.3af)
Power Consumption	Max 3.7W
Working Environment	-30°C~ +60°C, Less than 95% RH
Ingress Protection	IP67
Vandal Resistance	N/A
Dimensions	Φ 106mm x 94mm
Weight	0.47kg(0.65kg with package)

OUR LOCATION

1300 N. FLORIDA MANGO RD
SUITE 14A
WEST PALM BEACH, FL 33409



CCTV
AGENT

CONTACT INFO

TOLL FREE: 877.523.CCTV (2288)
MAIN : 561.249.4511
EMAIL : SALES@CCTVAGENT.COM